



DCH6416

Analog/Digital, HDTV, Dual-Tuner DVR, M-Card™ Host Set-top

The Motorola DCH6416 analog/digital HD DVR Host set-top provides a full set of SDTV, HDTV, and data features and interfaces. In addition to high-definition digital video, the DCH6416 provides superior analog picture quality with dual-channel 3-D comb filters and motion-compensating noise reduction. The DCH6416 supports a wide range of current and future interactive applications running on Motorola's existing DCT legacy APIs.

Features

M-Card (Multi-stream CableCARD) Host support for conditional access

Digital Video Recording (DVR) with support for dual recording and watch-and-record functionality

160 GB hard drive with shock mounting and fan

Compatible with Motorola DCT legacy APIs

Standard-definition (SD), enhanced-definition (ED), and high-definition (HD) MPEG-2 video support with output scaled to 480i, 480p, 720p, or 1080i

Dual 54 to 864 MHz video tuners

Digital video (64 QAM/256 QAM)

Video scaling (Picture-in-Graphics)

Accelerated graphics

Motion-compensating temporal filter video noise reduction

Motion-adaptive de-interlacing

Dual channel 3-D comb filter for state-of-the-art color and resolution

Dual MPEG-2 encoders for analog content

Dolby™ Digital 5.1 and PCM audio

16 MB Flash (standard)

128 MB DRAM total (standard)

DOCSIS® 2.0 cable modem with support for DSG

RF out-of-band (OOB) data transmitter/receiver

On-screen diagnostics

Macrovision™, HDCP, 5C DTCP, and CGMS-A content protection schemes on the respective interfaces

Full-featured front panel display and controls

SPECIFICATION SHEET
DCH6416 Set-top Box

STANDARD INTERFACES

Front Panel	On/Standby and Message indicators, output video format indicator, 4-character 7-segment display, 2 recording indicators, IR remote control sensor, USB 2.0 Host Type A port
Rear Panel	F-connector for cable input, M-Card slot, RF remodulated output (Ch 3/4), HDMI output, YPbPr component output, baseband composite video output, S-video output, L/ R audio output, coaxial and optical S/PDIF digital audio outputs, USB 2.0 Host Type A port, 1394a interfaces (2), 10/100 Mbps Ethernet interface, eSATA interface, mini-phone serial port

MANUFACTURING OPTIONAL FEATURES

M-Card pre-installed, 256 MB DRAM (upgrade from 128 MB)

SPECIFICATIONS

RF Input Frequency	54 to 864 MHz
Memory	16 MB Flash; 128 MB DRAM standard unified
Legacy Platform	Supported
Video	Up to 32-bit color, accelerated 2-D support, and scalable video-in-graphics
Processor	MIPS, RISC-based
Graphics Resolution	
SD Outputs	4:3 up to 720x480
HD Outputs	16:9 up to 1920x1080
Video Resolution	480i, 480p, 720p, and 1080i
Operating Temperature	15 °C to 42 °C (50 °F to 108 °F)
Operating Humidity	5 to 90% (non-condensing)
AC Voltage	105 to 125 VAC, 60 Hz
Power Dissipation	46 W (depending on features)
OOB Modulation	QPSK
Frequency	Agile receiver 70 to 130 MHz
Bandwidth	2.0 MHz maximum
Level	-15 to 15 dBmV
Digital Input Level	
64 QAM	-15 to 15 dBmV
256 QAM	-12 to 15 dBmV
Dimensions	17.2 in W x 12.70 in D x 2.76 in H (43.23 cm x 32.26 cm x 7.01 cm)
Weight	12.0 lb (5.4 kg)

Certain features may not be activated by your service provider, and/or their network settings may limit the feature's functionality. Additionally, certain features may require a subscription. Contact your service provider for details.

All features, functionality, and other product specifications are subject to change without notice or obligation.



Motorola, Inc. 101 Tournament Drive, Horsham, Pennsylvania 19044 U.S.A. www.motorola.com

MOTOROLA and the Stylized M Logo are registered in the U.S. Patent and Trademark Office. Macrovision is a registered trademark of the Macrovision Corporation. Dolby is a trademark of Dolby Laboratories Licensing Corporation. HDMI, the HDMI logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. DOCSIS is a registered trademark of Cable Television Laboratories, Inc. M-Card is a trademark of Cable Television Laboratories, Inc. All other product or service names are the property of their respective owners. © Motorola, Inc. 2009. All rights reserved